

RUEDA DONA AMORTIGUADA



- High modulus quality rubber tread vulcanized to aluminum core.
- Rounded balloon cushion tread offers the best shock absorbing cushioned ride available, easily rolls over debris and small obstructions (electrical cords, floor joints, etc), offers maximum floor protection, high impact strength and ultra quiet rolling operation.
- High modulus round tread minimizes surface friction and enables wheel to turn easily.
- Gray & black tread colors are available; gray tread is non-marking.
- To maximize roll-ability, we recommend using # 63 Sealed precision ball bearings with top hat bushings.
- Durometer: 60 Shore A (+/-5).
- Temperature range: -40° F to 180° F.

| Wheel Diameter | Tread Width | Hub Length | Load Capacity | Part Number <i>Replace + with Color Code</i> | Color Code | Replace ** with desired bearing code. | | | |
|----------------|-------------|------------|---------------|---|------------|---------------------------------------|-------------------------|-----------------|-----------------|
| | | | | | | Plain Bore | Precision Ball Bearings | Roller Bearings | Delrin Bearings |
| 6 | 2 | 2-3/16 | 350 | BC60J+** | X, Z | 84 | 63, 72 | 02,04,05,09,92 | 56,57,11,12 |
| 8 | 2 | 2-3/16 | 450 | BC80J+** | | 84 | 63, 72 | 02,04,05,09,92 | 56,57,11,12 |

| Bore & Bearing Sizes | | | | | | | | | | | | |
|----------------------|-----------------|-----|----------------------|----------------------|------------------------|-----|----------------------|-----|-----------------------------|----------------------------------|------------|--|
| Bearing/Bore Code | 02 | 04 | 05 | 09 | 11 | 12 | 56 | 57 | 63 | 72 | 84 | 92 |
| Bearing / Bore Type: | Roller Bearings | | S.S. Roller Bearings | Caged Roller Bearing | 1 Piece Delrin Bearing | | 2 PC Delrin Bearings | | Prec. BB w/top hat bushings | S.S. Prec. BB w/top hat bushings | Plain Bore | 3/4 I.D. Roller Bearing w/Stl. Bushing |
| Inner Diameter: | 5/8 | 3/4 | 3/4 | 3/4 | 3/4 | 1/2 | 1/2 | 3/4 | 1/2 | 1/2 | 1-3/16 | 1/2 |

