

RUEDA TERMOPLÁSTICA REFORZADA

NEW!



- Injection molded reinforced thermoplastic wheel has the same weight capacity of steel, yet incredibly light-weight and impact resistant.
- Hard tread and precision bearings; offer a smooth ergonomic ride, requires less effort to start up and maintain a rolling load.
- 100% washable & steam cleanable; has the best chemical resistance of any wheel, not affected by grease, oils, most chemicals & cleaning solutions, salt, brine & blood.
- Extreme impact strength, good abrasion and compression resistance, will not flat spot.
- Durometer: 65 Shore D (+/-5).
- Temperature range: -45° F to 250° F



Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number	Replace ** with desired bearing code.			
					Plain Bore	Roller Bearings	Precision Bearings	Delrin Bearings
4	2	2-3/16	800	HI40JB**	84	02,04,05,09,92	60,6S,63,72	56,57,11,12
5	2	2-3/16	1000	HI50JB**	84	02,04,05,09,92	60,6S,63,72	56,57,11,12
6	2	2-3/16	1200	HI60JB**	84	02,04,05,09,92	60,6S,63,72	56,57,11,12
8	2	2-3/16	1400	HI80JB**	84	02,04,05,09,92	60,6S,63,72	56,57,11,12

Bore & Bearing Sizes														
Bearing/Bore Code	02	04	05	09	11	12	56	57	60	6S	63	72	84	92
Bearing / Bore Type:	Roller Bearings		S.S. Roller Bearings	Caged Roller Bearing	1 Piece Delrin Bearing		2 PC Delrin Bearings		Sealed Prec. BB (Flanged)	S.S. Sealed Prec. BB (Flanged)	Sealed Prec BB w/top hats	S.S. Sealed Prec BB w/top hats	Plain Bore	3/4 I.D. Roller Bearing w/Stl. Bushing
Inner Diameter:	5/8	3/4	3/4	3/4	3/4	1/2	1/2	3/4	1/2	1/2	1/2	1/2	1-3/16	1/2