

RUEDA V-GROOVE FIBRA DE NYLON



- Injection molded ultra-strong, glass filled nylon wheel has the same weight capacity of steel, yet incredibly light-weight.
- Rust free material makes this the perfect wheel for outdoor applications.
- 100% washable & steam cleanable; not effected by grease, oils, most chemicals & cleaning solutions, salt, brine & blood.
- Extreme impact strength and abrasion and compression resistance.
- Durometer: 85 Shore D (+/-5).
- Temperature range: -45° F to 250° F

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number	Replace ** with desired bearing code.			
					Plain Bore	Roller Bearings	Precision Bearings	Delrin Bearings
4	1-1/2	1-5/8	600	MV40HT**	84	01,03		56,57,11,12
4	2	2-3/16	800	MV40JT**	84	02,04,05,09,92	60, 6S	56,57,11,12

Bore & Bearing Sizes														
Bearing/Bore Code	01	02	03	04	05	09	11	12	56	57	60	6S	84	92
Bearing / Bore Type:	Roller Bearings				S.S. Roller Bearings	Caged Roller Bearing	1 PC Delrin Bearing	2 PC Delrin Bearings	Sealed Prec. BB	S.S. Sealed Prec. BB	Plain Bore	3/4 I.D. Roller Bearing w/Bushing		
Inner Diameter:	5/8	5/8	3/4	3/4	3/4	3/4	3/4	1/2	1/2	3/4	1/2	1/2	1-3/16	1/2