

# RUEDA DE NYLON



- Solid wheel molded from Nylon 6.
- 100% washable & steam cleanable; impervious to water, highly resistant to organic solvents, most chemicals & cleaning solutions; ideal for use in food processing and packaging plants.
- Offers high impact strength and exceptional abrasion resistance.
- Hard tread has slight crown and rolls very easily.
- Non-marking.
- Durometer: 75 Shore D (+/-5).
- Temperature range: -40° F to 210° F.

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number	Replace ** with desired bearing code.				
					Plain Bore	Ball Bearings	Roller Bearings	Precision Bearings	Delrin Bearings
3	1-1/4	1-9/16	300	NY30GE**	83, 90	42			
3-1/2	1-1/4	1-9/16	325	NY35GE**	83, 90				
4	1-1/4	1-9/16	350	NY40GE**	83, 90	42			
5	1-1/4	1-9/16	500	NY50GE**	83, 90	42			
4	2	2-3/16	800	NY40JE**	84		02,04,05,09	60,6S,72	56,57,11,12
5	2	2-3/16	900	NY50JE**	84		02,04,05,09	60,6S,72	56,57,11,12
6	2	2-3/16	1000	NY60JE**	84		02,04,05,09	60,6S,72	56,57,11,12
8	2	2-3/16	1100	NY80JE**	84		02,04,05,09	60,6S,72	56,57,11,12

Bore & Bearing Sizes																
Code	02	04	05	09	11	12	42	56	57	60	6S	72	83	84	90	92
Bearing or Bore Type:	Roller Bearings		S.S. Roller Bearings	Caged Roller Bearing	1 Piece Delrin Bearing		Ball Bearing	2 PC Delrin Bearings		Sealed Prec. BB (Flanged)	S.S. Sealed Prec. BB (Flanged)	S.S. Sealed Prec BB w/top hats	Plain Bore		1/2 Plain with Bushing	3/4 I.D. Roller Bearing w/Stl. Bushing
Inner Diameter:	5/8	3/4	3/4	3/4	3/4	1/2	3/8	1/2	3/4	1/2	1/2	1/2	1/2	1-3/16	3/8	1/2