

RUEDA DE POLIURETANO EN ALUMINIO



- Polyurethane elastomer tread chemically bonded to a light-weight aluminum core.
- Aluminum core has a strong attractive appearance, is lightweight and is resistant to rust and corrosion.
- Colors: Available in non-marking red & green tread for 2" face and blue in the 1-1/4 tread.
- Durometer: 95 Shore A (+/-5).
- Temperature range: -40° F to 180° F.

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number <i>Replace + with Color Code</i>	Color Code	Replace ** with desired bearing code.				
						Plain Bore	Annular Ball Bearings	Precision Ball Bearings	Roller Bearings	Delrin Bearings
3	1-1/4	1-9/16	380	PA30GL43	Blue		43			
3.5	1-1/4	1-9/16	400	PA35GL43			43			
4	1-1/4	1-9/16	420	PA40GL43			43			
5	1-1/4	1-9/16	440	PA50GL43			43			
4	1-1/2	1-5/8	700	PA40H+**	Green = N Red = R	84		60, 6S	01, 03	56,57,11,12
4	2	2-3/16	800	PA40J+**		84		60, 6S	02,04,05,09,92	56,57,11,12
5	1-1/2	1-5/8	800	PA50H+**		84		60, 6S	01, 03	56,57,11,12
5	2	2-3/16	900	PA50J+**		84		60, 6S	02,04,05,09,92	56,57,11,12
6	1-1/2	1-5/8	900	PA60H+**		84		60, 6S	01, 03	56,57,11,12
6	2	2-3/16	1200	PA60J+**		84		60, 6S	02,04,05,09,92	56,57,11,12
8	2	2-3/16	1500	PA80J+**		84		60, 6S	02,04,05,09,92	56,57,11,12

Bore & Bearing Sizes															
Bearing/Bore Code	01	02	03	04	05	09	11	12	43	56	57	60	6S	84	92
Bearing / Bore Type:	Roller Bearings				S.S. Roller Bearings	Caged Roller Bearing	1 Piece Delrin Bearing	Annular Ball Bearings	2 PC Delrin Bearings	Sealed Prec. BB (Flanged)	S.S. Sealed Prec. BB (Flanged)	Plain Bore	3/4 I.D. Roller Bearing w/Std. Bushing		
Inner Diameter:	5/8	5/8	3/4	3/4	3/4	3/4	3/4	1/2	3/8	1/2	3/4	1/2	1/2	1-3/16	1/2