

# RUEDA DE POLIURETANO SOLIDO



- Solid cast polyurethane elastomer one piece design eliminates bonding failures and is a very reliable and durable wheel.
- 100% washable & steam cleanable; not affected by grease, oils, most chemicals & cleaning solutions, brine & blood.
- Offers a smooth effortless ride, is non-marking and protects floors.
- Resists compression set or “flat spotting”, has exceptional impact strength and is highly abrasion resistant.
- Color: Blue
- Durometer: 60 Shore D (+/-5).
- Temperature range: -50° F to 180° F.

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number	Replace ** with desired bearing code.			
					Plain Bore	Roller Bearings	Precision BB	Delrin Bearings
3	1-1/4	1-9/16	300	SU30GL**	83, 90			
4	1-1/4	1-9/16	400	SU40GL**	83, 90			
5	1-1/4	1-9/16	700	SU50GL**	83, 90			
4	2	2-3/16	750	SU40JL**	84	02,04,05,09,92	60,6S,72	56,57,11,12
5	2	2-3/16	900	SU50JL**	84	02,04,05,09,92	60,6S,72	56,57,11,12
6	2	2-3/16	1000	SU60JL**	84	02,04,05,09,92	60,6S,72	56,57,11,12
8	2	2-3/16	1000	SU80JL**	84	02,04,05,09,92	60,6S,72	56,57,11,12

See above for bearing specifications