

RUEDA DE FIBRA NYLON ALTA TEMPERATURA



- **Brimstone®** wheels are made out of an exclusively engineered thermo compound made for high temperature, autoclave and steam cleaning wash down applications -not recommended for prolonged dry heat environments.
- Offers superior abrasion and impact resistance, high weight capacity and long service life.
- Excellent resistance to oil, grease, salt and most acids, chemicals and cleaning solutions.
- Hard tread rolls exceptionally easy.
- Durometer: 85 Shore D (+/-5).
- Temperature range: -45° F to 425° F.

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number	Replace ** with desired bearing code.		
					Plain Bore	Roller Bearings	Precision BB
3	1-1/4	1-3/8	300	GN30GQ**	83,97,99		
3	1-1/2	1-5/8	600	GN30HQ**	83		
3.5	1-1/4	1-3/8	300	GN35GQ**	83,97,99		
4	1-1/4	1-3/8	300	GN40GQ**	83,97,99		
4	1-1/2	1-5/8	700	GN40HQ**	83,88,84	01,03	
4	2	2-3/16	800	GN40JQ**	84,88	02,04,05,09,92	60,6S
5	1-1/4	1-3/8	700	GN50GQ**	83,97,99		
5	1-1/2	1-5/8	800	GN50HQ**	83,84	01,03	
5	2	2-3/16	1000	GN50JQ**	84,88	02,04,05,09,92	60,6S
6	2	2-3/16	1100	GN60JQ**	84,88	02,04,05,09,92	60,6S
8	2	2-3/16	1200	GN80JQ**	84,88	02,04,05,09,92	60,6S

