

# RUEDA DONA AMORTIGUADA



- High modulus quality rubber tread vulcanized to aluminum core.
- Rounded balloon cushion tread offers the best shock absorbing cushioned ride available, easily rolls over debris and small obstructions (electrical cords, floor joints, etc), offers maximum floor protection, high impact strength and ultra quiet rolling operation.
- High modulus round tread minimizes surface friction and enables wheel to turn easily.
- Gray & black tread colors are available; gray tread is non-marking.
- To maximize roll-ability, we recommend using # 63 Sealed precision ball bearings with top hat bushings.
- Durometer: 60 Shore A (+/-5).
- Temperature range: -40° F to 180° F.

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number <i>Replace + with Color Code</i>	Color Code	Replace ** with desired bearing code.			
						Plain Bore	Precision Ball Bearings	Roller Bearings	Delrin Bearings
6	2	2-3/16	350	BC60J+**	X, Z	84	63, 72	02,04,05,09,92	56,57,11,12
8	2	2-3/16	450	BC80I+**		84	63, 72	02,04,05,09,92	56,57,11,12

Bore & Bearing Sizes												
Bearing/Bore Code	02	04	05	09	11	12	56	57	63	72	84	92
Bearing / Bore Type:	Roller Bearings		S.S. Roller Bearings	Caged Roller Bearing	1 Piece Delrin Bearing		2 PC Delrin Bearings		Prec. BB w/top hat bushings	S.S. Prec. BB w/top hat bushings	Plain Bore	3/4 I.D. Roller Bearing w/Stl. Bushing
Inner Diameter:	5/8	3/4	3/4	3/4	3/4	1/2	1/2	3/4	1/2	1/2	1-3/16	1/2

