

RUEDAS NEUMÁTICAS



OFFSET
Wheels for
Hand Trucks

**BRASS
PLATED
HUBS
ALSO AVAILABLE.**

- Wheels come with outer tire, inner tube and are mounted on either centered or offset rims/hubs; centered rims for mounting in casters & equipment and offset rims for use on hand trucks & portable equipment.
- Pneumatic wheels offer the maximum cushion ride available and easily roll over debris and small obstacles, great for both indoor and outdoor use; provides good floor protection and quiet rolling operation
- Wheels are available with several tread patterns and colors; black tread wheels can mark floors. Gray wheels are non-marking on most surfaces as long as they are clean. Rims are made out of high quality heavy duty steel, offering exceptional reliability.
- Standard sizes and designs are listed; however custom wheels are available upon request, please inquire.

Wheel Part# Explanation

FP 8 B 4 C P3

Pneumatic | Tire Size | Ply Rating | Bearing | Tread Pattern | Characteristic Combination

Tire Size Part# Abbreviations

Part# Abbrev.	Tire Specification & Approximate Diameter
5	250-4 (8")
8	280-4 (8")
0	350-4 (10")
2	350-6 (12")
6	480-8 (16")

Wheel Characteristic /Codes.

Tire Color	Hub Finish	Hub Design
B = Black	BR = Brass	C = Centered
G = Gray	W = White	O = Offset
	Z = Zinc	

Wheel Characteristic Combinations

Part# Abbreviations

Part# Abbrev.	Code Combinations (#From above table)
C	B - Z - C
D	G - Z - O
F	B - BR - C
G	B - G - O
K	B - G - C
O	B - Z - O
R	G - BR - C
T	B - W - C
W	B - W - O
Y	G - Z - C

Tire Spec & Approx. Diameter	Tread Pattern	Ply Rating	PSI	Hnb Length	Hub Design	Hub Type	Load Cap.	Color	Part Number	Replace ** with desired bearing code.			
										Plain Bore	Roller Bearings	Ball Bearings	Precision BB.
6 X 2	F	4	30	2-1/2	Centered	2-PC	200	Black/Zinc	FP60J B60				60
250-4 (8")	B	2	50	3-1/4	Centered	3-PC	250	Black/Zinc	FP5E2C**	95		51,52,53	P1,P2, P3
280-4 (8")	A	4	50	3-3/16	Centered	3-PC	250	Black/Zinc	FP8A4C**	95	38	51,52,53	P1,P2, P3
280-4 (8")	A	4	50	3-3/16	Centered	3-PC	250	Black/Brass	FP8A4P**	95	38	51,52,53	P1,P2, P3
280-4 (8")	A	4	50	3-3/16	Centered	3-PC	250	Gray/Zinc	FP8A4Y**	95		51,52,53	P1,P2, P3
280-4 (8")	A	4	50	3-3/16	Centered	3-PC	250	Gray/ Brass	FP8A4R**	95		51,52,53	P1,P2, P3
280-4 (8")	A	4	50	2-1/4	Offset	3-PC	250	Black/Zinc	FP8A4O**	95		51,52,53	P1,P2, P3
280-4 (8")	A	4	50	2-1/4	Offset	3-PC	250	Gray/Zinc	FP8A4D**	95		51,52,53	P1,P2, P3
350-4 (10")	D	4	50	4	Centered	3-PC	350	Gray/Zinc	FP0D4Y**	95		51,52,53	P1,P2, P3
350-4 (10")	D	4	50	4	Centered	3-PC	350	Black/Zinc	FP0D4C**	95	40	51,52,53	P1,P2, P3
350-4 (10")	D	4	50	2-1/4	Offset	3-PC	350	Black/Zinc	FP0D4O**	95		51,52,53	P1,P2, P3
350-4 (10")	G	4	50	2-1/4	Offset	3-PC	350	Gray/Zinc	FP0G4D**	95		51,52,53	P1,P2, P3
350-4 (10")	E	6	75	2-1/4	Offset	3-PC	400	Black/Zinc	FP0E6O**	95		51,52,53	P1,P2, P3
350-4 (10")	E	6	75	4	Centered	3-PC	400	Black/Zinc	FP0E6C**	95	40	51,52,53	P1,P2, P3
350-4 (10")	E	4	50	2-1/4	Offset	1-PC	350	Black/White	FP0E4W**	95		51,52,53	P1,P2, P3
350-4 (10")	C	4	50	2-1/4	Offset	1-PC	350	Black/White	FP0C4W**	95		51,52,53	P1, P2, P3
350-4 (10")	C	4	50	2-1/4	Offset	1-PC	350	Black/Gray	FP0C4G**	95		51,52,53	P1,P2, P3
350-6 (12")	D	4	50	4	Centered	1-PC	460	Black/White	FP2D4T**	95		51,52,53	P1,P2,P3
350-6 (12")	E	6	85	4	Centered	1-PC	500	Black/White	FP2E6T**	95		51,52,53	P1,P2,P3
350-6 (12")	C	4	50	4	Centered	1-PC	460	Black/White	FP2C4T**	95		51,52,53	P1,P2, P3
480-8 (16")	C	4	42	3	Centered	1-PC	500	Black/White	FP6C4T**	95		51,52,53	P1,P2, P3
480-8 (16")	C	6	75	3	Centered	1-PC	650	Black/White	FP6C6T**	95		51,52,53	P1,P2, P3

TREAD PATTERNS



Bore & Bearing Sizes										
Bearing Code:	38	40	51	52	53	60	P1	P2	P3	95
Bearing Type:	Roller Bearings		Ball Bearings			Prec. Ball Bearings			Plain Bore	
Inner Diameter	3/4	3/4	1/2	5/8	3/4	1/2	1/2	5/8	3/4	1-3/8