

RUEDA DE NYLON



- Solid wheel molded from Nylon 6.
- 100% washable & steam cleanable; impervious to water, highly resistant to organic solvents, most chemicals & cleaning solutions; ideal for use in food processing and packaging plants.
- Offers high impact strength and exceptional abrasion resistance.
- Hard tread has slight crown and rolls very easily.
- Non-marking.
- Durometer: 75 Shore D (+/-5).
- Temperature range: -40° F to 210° F.

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number	Replace ** with desired bearing code.				
					Plain Bore	Ball Bearings	Roller Bearings	Precision Bearings	Delrin Bearings
3	1-1/4	1-9/16	300	NY30GE**	83, 90	42			
3-1/2	1-1/4	1-9/16	325	NY35GE**	83, 90				
4	1-1/4	1-9/16	350	NY40GE**	83, 90	42			
5	1-1/4	1-9/16	500	NY50GE**	83, 90	42			
4	2	2-3/16	800	NY40JE**	84		02,04,05,09	60,6S,72	56,57,11,12
5	2	2-3/16	900	NY50JE**	84		02,04,05,09	60,6S,72	56,57,11,12
6	2	2-3/16	1000	NY60JE**	84		02,04,05,09	60,6S,72	56,57,11,12
8	2	2-3/16	1100	NY80JE**	84		02,04,05,09	60,6S,72	56,57,11,12

Bore & Bearing Sizes																
Code	02	04	05	09	11	12	42	56	57	60	6S	72	83	84	90	92
Bearing or Bore Type	Roller Bearings		S.S. Roller Bearings	Caged Roller Bearing	1 Piece Delrin Bearing		Ball Bearing	2 PC Delrin Bearings		Sealed Prec. BB (Flanged)	S.S. Sealed Prec. BB (Flanged)	S.S. Sealed Prec BB w/rop hats	Plain Bore		1/2 Plain with Bushing	3/4 I.D. Roller Bearing w/Stl. Bushing
Inner Diameter:	5/8	3/4	3/4	3/4	3/4	1/2	3/8	1/2	3/4	1/2	1/2	1/2	1/2	1-3/16	3/8	1/2