

Wheels: POLYMADIC™ Premium Polyurethane

NEW!



- High performance UV resistant, liquid cast polyurethane elastomer; mechanically locked onto an injection molded polyolefin core; takes more abuse and has a longer service life than standard PP wheels.
- 1-1/4" wide wheels are Maroon on gray, with sanitary style (no thread guards) dished out core and dual row annular ball bearings, offering improved mobility and stability- axle can be completely tightened without binding the bearings. 2 inch wide wheels have a dark gray tread on a gray core.
- Optional No Seam style available (for upcharge): No seam on the wheel tread reduces the possibility of leaving indentions on soft floors (wood, linoleum, etc). Change wheel designation to "PS"
- Durometer: 60 Shore D (+/-5).
- Temperature range: -45° F to 180° F.

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number <i>Replace + with Color Code</i>	Color Code	Replace ** with desired bearing code.				
						Plain Bore	Dual Row Annular BB	Roller Bearings	Precision Ball Bearings	Delrin Bearings
3	1-1/4	1-9/16	260	PM30GM43	Maroon on Gray		43			
3-1/2	1-1/4	1-9/16	270	PM35GM43	Maroon on Gray		43			
4	1-1/4	1-9/16	325	PM40GM43	Maroon on Gray		43			
5	1-1/4	1-9/16	340	PM50GM43	Maroon on Gray		43			
4	2	2-3/16	600	PM40JI**	Gray on Gray	84	48	02,04,05,09,92	60,6S,63,73	56,57,11,12
5	2	2-3/16	750	PM50JI**	Gray on Gray	84	48	02,04,05,09,92	60,6S,63,73	56,57,11,12
6	2	2-3/16	900	PM60JI**	Gray on Gray	84	48	02,04,05,09,92	60,6S,63,73	56,57,11,12
8	2	2-3/16	*1000	PM80II**	Gray on Gray	84	*48	02,04,05,09,92	60,6S,63,73	56,57,11,12

*Capacity of 48 annular bearing is 900 lbs.