

RUEDA DE POLIURETANO EN FIBRA DE NYLON



- Polyurethane elastomer tread chemically bonded to an ultra-strong mag style glass filled nylon core that has the same weight capacity of steel; light-weight yet very durable
- Offers a smooth effortless ride, is non-marking and protects floors.
- Resists compression set or “flat spotting”, has exceptional impact strength and good abrasion resistance.
- Non-metal materials will not rust.
- Colors: Red & green.
- Durometer: 95 Shore A (+/-5).
- Temperature range: -45° F to 180° F.

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number <i>Replace + with Color Code</i>	Color Code	Replace ** with desired bearing code.			
						Plain Bore	Roller Bearings	Precision BB	Delrin Bearings
4	2	2-3/16	700	MU40J+**	Green = G Red = K	84	02,04,05,09,92	60,6S,72	56,57,11,12
5	2	2-3/16	1000	MU50J+**		84	02,04,05,09,92	60,6S,72	56,57,11,12
6	2	2-3/16	1200	MU60J+**		84	02,04,05,09,92	60,6S,72	56,57,11,12
8	2	2-3/16	1400	MU80J+**		84	02,04,05,09,92	60,6S,72	56,57,11,12

Bore & Bearing Sizes														
Bearing/Bore Code	02	04	05	09	11	12	56	57	60	6S	63	72	84	92
Bearing / Bore Type:	Roller Bearings		S.S. Roller Bearings	Caged Roller Bearing	1 Piece Delrin Bearing		2 PC Delrin Bearings		Sealed Prec. BB (Flanged)	S.S. Sealed Prec. BB (Flanged)	Sealed Prec BB w/top hats	S.S. Sealed Prec BB w/top hats	Plain Bore	3/4 I.D. Roller Bearing w/Stl. Bushing
Inner Diameter:	5/8	3/4	3/4	3/4	3/4	1/2	1/2	3/4	1/2	1/2	1/2	1/2	1-3/16	1/2